


# **ESC200**

# Dolby Pro-Logic® Surround Processor/Amplifier

# SERVICE MANUAL



JBL Consumer Products Inc. 250 Crossways Park Drive Woodbury, N.Y. 11797 1-800-336-4JBL in the USA

H A Harman International Company

Part No.: 1112-ESC200 Rev A 10/98

# **TABLE OF CONTENTS**

ESC200 SPECIFICATIONS1	ESC200 KEYPAD PCB10
CONTROLS AND THEIR FUNCTION3	ESC200 MAIN PCB (Component Side)11
ESC200 SPEAKER AND SOURCE CONNECTIONS3	ESC200 MAIN PCB (Solder Side)12
ESC200 PACKING4	INTEGRATED CIRCUIT DIAGRAMS13
ESC200 BLOCK DIAGRAM5	SCHEMATIC DIAGRAMS16
ESC200 UNIT EXPLODED VIEW6	ESC200 IC VOLTAGE READINGS23
ESC200 PARTS LISTS7	

# **ESC200 SPECIFICATIONS**

	Satellite Speaker	Subwoofer
Power Handling (RMS)	20 Watts	60 Watts
Frequency Response	120Hz - 20kHz	35Hz - 200Hz
Sensitivity (1 Watt/1 meter)	87dB	90dB
Nominal Impedance	8 ohms	6 ohms
Woofer Size	3"	6-1/2"
Tweeter Size	1"	
Dimensions (HxWxD)	4-1/16 x 7-1/2 x 7-3/8" 103 x 190 x 187mm	

#### **Processor Amplifier**

Total Maximum Amplifier Output - 100 Watts

Dimensions (HxWxD) - 2-11/16 x13-1/2 x 9" (69 x 343 x 230mm)

Occasional refinements may be made to existing products without notice, but will always meet or exceed original specifications unless otherwise stated.

# **ESC200 SPECIFICATIONS**

ESC200 Pro-Logic Surround Theater System

Power source: 117V/60Hz 230Hz/50Hz

Test conditions: 8 ohm loading each channel (6X)

Bass & Treble - flat

Boost - off Mode - stereo

Fader - front channel = back channel

Balance - left = right


Volume - 300 mV input for 1W (to nearest step)

Center Trim - center Surround Trim - center

#### **Technical Performance Readings**

Parameter	rs	Unit	Typical	Limit
1. THD at 8W, 1KHz, outp	%	0.5%	1%	
2. THD at 15W, 50Hz, Sul	o out	%	1.0%	3%
3. Frequency Response at re 1KHz, -3dB	t five output a. b.	Hz Hz	125 50K	100-150 >30K
Frequency Response at re 50Hz, -3dB	t five output a. b.	Hz Hz	110 18	85-125 <25
5. Volume Control at 1KHz	z (from Max)	db	60	>50
6. Balance Control at 1KH	Z	db	40	>30
7. Fader Control at 1KHz		db	40	>30
8. Bass a. Boost at 10 b. Cut at 100h	0Hz Iz (Bass control)	db db	7 10	>5 >8
9. Treble a. Boost at 10 b. Cut at 10Kh	KHz Hz (Treble control)	db db	8 8	>6 >6
10. Bass Boost at 80Hz (E	Boost function)	db	6	>5
11. Input Z at 1KHz	a. Input 1 b. Input 2	ohm ohm	20K 20K	>15K >15K
12. S/N Ratio "A" re 1W ir	put short	db	72	>70
13. Noise level w/30K LPF	input short	mV	0.8	1.0
14. S/N Ratio "A" re 1W Surround Mod Input Short Su	db db	70 63	>65 >60	
15. Noise level w/30K LPF Surround Mod Input Short Su	e L, C, R, SUB	mV mV	1.2 1.5	1.5 2.0
16. Input Sensitivity at 8W (Vol at Max, 1kHz) at Fl	mV	350	270-420	
17. Separation at 1W, 1kH	łz	db	45	>40


# **CONTROLS AND THEIR FUNCTION**




- VOLUME This controls an increase (+) or decrease (-) in volume.
- CENTER This controls the volume of the Center Speaker.
- 3. TREBLE This controls the level of the treble.
- 4. BASS This controls the overall bass output.
- 5. **BASS BOOST** This increases the bass output to the subwoofer.
- 6-9. **BALANCE** These buttons balance the front and rear as well as the left and right speaker strengths.


- 10. STEREO This turns on and off the stereo mode.
- 11. **HALL** This changes the sound to Hall mode.
- 12. **CONCERT** This changes the sound to Concert mode.
- 13. PRO-LOGIC This turns on the Pro-Logic mode.
- 14. **INPUT 1/2** This swiches to either music source connected to Input 1 or Input 2 (RCA jacks).
- 15. POWER This button turns on the ESC200.

#### **ESC200 SPEAKER AND SOURCE CONNECTIONS**







### **ESC200 PACKING**



# **ESC200 BLOCK DIAGRAM**



# **ESC200 UNIT EXPLODED VIEW**



# ESC200 PARTS LISTS

Ref. #	Part #	Description	Qty	Ref. #	Part #	Description (	Qty
				C56	1-12147LI	47μF 16V+-20% 5x11	1
				C59, 143	1-12210KI	100μF 10V+-20% 5x11	2
MAIN-PCB SE	CTION			C63, 141	1-12247MI	470μF 25V+-20% 8x16	2
Conscitors				C90, 91	1-16110PH	100ρF 50V+- 10%	2
Capacitors C1, 2, 35, 60, 86, 158, 179	1-12010PI	1μF E.CAP, 50V+-20% 5x11	7	C109, 119, 120, 127, 128, 133	1-12133NI	33μF 35V+-20% 6x11	6
C3	1-12310KI	1000μF 10V+-20% 8x16	1	C139, 148, 149, 172	1-12524MI	2200μF 25V+-20% 16x26 85C	4
C5, 199, 202, 205 208, 211, 214	1-11447RH	0.0047μF 100V+-10% MINI	7	C177, 186, 187, 188, 189, 190, 197	1-11201RH	0.01μF 100V+-10% MINI	7
C6, 11, 21, 24, 25	1-11122RH	0.22μF 100V+-10%MINI	10	C181	1-12922PI	22μF 50V+-20% 5x11 LL	1
97, 102, 118, 126, 154				C191, 192, 193, 194, 195	1-16115PH	150pF 50V +-10% CERAMIC	5
C7, 48, 73, 77, 144, 153, 165	1-11322RH	0.022μF 100V+-10% MINI	7	C198, 201, 204, 207, 210, 213	1-16122PH	220ρF 50V +-10% CERAMIC	6
C8, C27, C31, C54, C55	1-11347RH	0.047μF 100V+-10% MINI	5	C200, 203, 206, 209 212, 215, 216	1-16301PH	0.001μF 50V +-10% CERAMIC	7
C9, 41, 43, 61, 104, 178, 180	1-14091PI	0.1μF MONO CAP 50V +-20% HB-TYPE	7	C221	1-16010PH	10pF 50V +-10% CERAMIC	1
C10, 12	1-12122LI	22μF 16V+-20% 5x11	2	Diodes			
C11, 39, 44, 45	1-12110LI	10μF 16V+-20% 5x11	26	D1, 2, 3, 4	1-05-031	DIODE 6A1-4	4
47, 62, 64, 66, 69, 70, 72, 88,				D5	1-05-009	DIODE 1N4148 T/R	1
89, 94, 98, 99, 103, 107, 115,				Z1, 2	1-06-001	ZENER 1/2W+-5% 5.1V T/R	2
123, 137, 140, 161, 162, 164, 171				Z3	1-06-003	ZENER, 1/2W+-5% 8.2V T/R	1
C13, 14, 16, 17	1-11101RH	0.1μF M.CAP, 100V+-10% MINI	33	Integrated Circuits	3		
20, 32, 33, 40, 53, 57, 80, 81,	1-111011111	0.1μ1 W.OAI , 100V+-1076 WIINI	33	U1	1-09-058	IC, NJM2177AL, DOLBY PRO-LOGIC SURROUND DECODER	C 1
82, 83, 84, 92, 93, 105, 106, 113, 114, 121,				U2	1-09-057	NJU9701D/NJU9702D DIGITAL DELAY	1
122, 129, 130, 150, 156, 182, 183, 184, 185,				U3	1-09-305	CD 4066D QUAD BILATERAL SWITCH	1
219, 220				U4	1-09-024	BA14741 ROHM QUAD OP AMP	1
C15, 67, 75, 79, 95, 96, 100, 108, 111, 116, 117,	1-12020PI	2.2μF 50V+-20% 5x11	20	U5, 10, 11, 12	1-09-421	BA4560/4560D ROHM/NJRC DUAL OP AMP	4
124, 125, 132, 136, 138, 147, 160, 167, 169				U6, 7, 8	1-09-054	LC7538NM SANYO, ELECTRONIC VOLUME CONTROL	3
C18, 19, 37, 38,	1-12047PI	4.7μF 50V+-20% 5x11	5	U9	1-09-053	LC7821N SANYO, ANALOG SWITCH	<del> </del> 1
101	1-1204/11	4.7μ1 30 ν τ-20 % 3λ11	3	U13, 14, 15	1-09-092	LM1876TF NS, 20W POWER AMP	3
C22	1-12968PI	0.68μF 50V+-20% 5x11 LL	1	U16	1-08-006	REG, NJM7809FA/7809A +9V REGULATOR	1
C23, 58, 87	1-16147PH	470ρF 50V+-10%	3	U17	1-08-158	REG, NJM7805FA/7805A	1
C26	1-11439RH	0.0039μF 100V+-10% MINI	1			+5V REGULATOR	
C28, 42	1-12220KI	220μF 10V+-20% 6x11	2	Resistors			
C29, 154, 155	1-11456RH	0.0056μF 100V+-10% MINI	3	R1, 2, 23, 27, 30,	1-17-415	1/8W+-5% PS 15K OHM T/B	9
C30	1-12002PI	0.22μF 50V+-20% 5x11	1	46, 47, 77, 79			
C36, 145	1-16168PH	680ρF 50V+-10%	2	R3, 4, 9, 10, 29, 35, 96, 104, 105,	1-17-482	1/8W+-5% PS 100K OHM T/B	12
C49, 74, 78, 152, 157, 166	1-11433RH	0.0033μF 100V+-10% MINI	6	120, 121, 122	4 47 440	A JOHN COV DO 401/ OLIVET TO	00
C50, 51	1-16031PH	30pF C.CAP, 50V+-10% NPO	2	R5, 6, 12, 25, 39, 54, 57, 67, 80, 90, 108,	1-17-410	1/8W+-5% PS 10K OHM T/B	22
C52, 63, 141, 142, 146	1-12247KI	470μF 10V+-20% 8x12	5	109, 111, 113, 123, 124, 125, 126, 164, 165, 166, 170			

Ref. #	Part #	Description	Qty	Ref. #	Part #	Description	Qty
R7, 8	1-17-510	1/8W+-5% PF 100K OHM	2				
R11	1-17-439	1/8W+-5% PS 39K OHM T/B	1	MISCELLANE	OUS SECT	'I∩N	
R15, 99	1-22-127	3W+-5% WIRE WOUND 27 OHM	2				
R16, 102	1-17-412	1/8W+-5% PS 12K OHM T/B	2	L1, 2, 3, 4, 5, 6	1-04-011	COIL, SPRING COIL 0.8mm 12T D=5.5mm	6
R17, 74	1-17-382	1/8W +-5% PS 8.2K OHM T/B	2	LD1	1-25-215	LED DISPLAY SET	1
R18, 78, 101, 110 R19, 51, 87, 92	1-17-422 1-17-327	1/8W+-5% PS 22K OHM T/B 1/8W+-5% PS 2.7K OHM T/B	4 4	XTAL1	1-03-109	C-RES, CER-RESONATOR, CSA2.0MHZ MURATA	1
R20	1-17-420	1/8W+-5% PS 20K OHM T/B	1			FLAT CABLE PITCH=2mm UL	
R21, 24, 69	1-17-375	1/8W +-5% PS 7.5K OHM T/B	3			3 PINS 160MM(10+10)	1
R22, 26	1-17-447	1/8W+-5% PS 47K OHM T/B	2		1-58-017	WAFER, 12 PINS PITCH=2.5mm	1
R28	1-17-647	1/8W+-5% PS 4.7M OHM T/B	1		1-58-010	WAFER, 3 PINS PITCH=2.5mm	1
R31, 33, 162,	1-17-351	1/8W +-5% PS 5.1K OHM T/B	8		1-58-009	WAFER, 4 PINS PITCH=2.5mm	1
163, 167, 168, 169, 171 R32, 34	1-17-510	1/8W+-5% PS 82K OHM T/B	2			FLAT CABLE PITCH=2.54mm 16 PINS 60MM(10+3) HOUSINGFEMALE/MALE	1
R36	1-17-610	1/8W+-5% PS 1M OHM T/B	1			HOUSING P=2.5mm	
R37, 55, 65,	1-17-324	1/8w+-5% PS 2.4K OHM T/B	5		1-51-372	SET, 12PINS 100mm FEMALE/MALE	1
88, 103 R38, 56, 66, 75	1-17-430	1/8W+-5% PS 30K OHM T/B	7		1-51-373	SET, 4PINS 200mm FEMALE/MALE	1
76, 89, 100 R40, 63	1-17-418	1/8W+-5% PS 18K OHM T/B	2		1-51-374	SET, 3PINS 160mm FEMALE/MALE	1
R41, 45, 52, 59, 64, 68, 73, 82, 86, 91, 97, 175	1-17-515	1/8W+-5% PS 150K OHM T/B	12		9-01-122	PCB, 2601-5P UL94V0 SWITCH PCB (230V)	1
R42, 49, 60, 70, 83, 93	1-19-010	1/2W+-5% PS 1 OHM T/B	6	1/5\/ DOD 05/			
R43, 50, 61, 71,	1-19-110	1/2W+-5% PS 10 OHM T/B	7	KEY PCB SEC	CTION		
84, 94, 98				C34	1-12110LI	E.CAP, 16V +-20% 5x11 10UF	1
R44, 62, 72	1-17-356	1/8W +-5% PS 5.6K OHM T/B	3	C168, 173	1-12220KI	10V +-20% 6x11 220UF	2
R48, 95	1-17-339	1/8W +-5% PS 3.9K OHM T/B	2	C174	1-12247KI	10V +-20% 8x12 470UF	1
R53, 58	1-17-120	RES, 1/8W+-5% PS 20 OHM T/B	2	C175, 176	1-16031PH	C.CAP, 50V+-10% 30PF NPO	2
R85, 112	1-17-215	1/8W+-5% PS 150 OHM T/B	2	PD1	1-05-039	PHOTO MODULE TSOP1838	1
R106, 107 R114, 115, 116,	1-17-312 1-17-310	1/8W+-5% PS 1.2K OHM T/B 1/8W+-5% PS 1K OHM T/B	2 4	R130, 132, 134, 136, 138, 140, 142, 144, 150	1-17-147	RES, 1/8W+-5% PS 47 OHM T/B	9
117	1 17 251	1/8W+-5% PF 5.1K OHM	2	R147, 148	1-17-247	1/8W +-5% PS 470 OHM T/B	2
R118, 119	1-17-351		2	R153, 174	1-17-310	1/8W +-5% PS 1K OHM T/B	2
R127	1-17-310	1/8W+-5% PF 1K OHM	1	R151	1-17-351	1/8W +-5% PS 5.1K OHM T/B	1
R128	1-17-433	1/8W+-5% PS 33K OHM T/B	1	R129, 131, 133,	1-17-410	1/8W +-5% PS 10K OHM T/B	13
R155	1-17-533	1/8W+-5% PS 330K OHM T/B	1	135, 137, 139, 141, 143, 156,			
R172, 173	1-17-410	1/8W+-5% PF 10K OHM	2	157, 158, 159, 160			
Transistors				R161	1-17-447	1/8W +-5% PS 47K OHM T/B	1
Q15, 16, 17, 18	1-07-004	NPN NEC 9014C	4	R154	1-17-610	1/8W +-5% PS 1M OHM T/B	1
Q19	1-07-107	NPN MPSA06	1	R152	1-17-147	1/8W +-5% PF 47 OHM	1
				R145, 146, 149	1-17-247	1/8W +-5% PF 470 OHM	3
				Q1, 2, 3, 4, 5, 6, 7, 8	1-07-003	NPN NEC 9013H	8
				Q9, 10, 11, 12, 13	1-07-002	PNP NEC 9012H	5


Ref. #	Part #	Description	Qty	Ref. #	Part #	Description	Qty
Q14	1-07-001	NPN NEC 9011G	1	30	1-33-465	SCREW 3x16 PM BZ FOR IC BRACKET	3
U18	1-09-056A	IC, UPD75106CW-240 NEC -2552B MICROPROCESSOR	1	31	1-37-230	M3 SPRING WASHER ZNC	3
XTAL2	1-03-107	CER-RESONATOR,	1	32	1-37-130	M3 FLAT WASHER BZ	7
		CSA4.19MHZ MURATA		33	1-37-030	M3 NUT	3
				34	1-27-076	POWER SWITCH (ONLY ON 230V)	1


# **MECHANICAL PARTS LIST**


PANIS LI	<b>ा</b>	
5-01-257 5-01-262	120V TOP COVER 230V TOP COVER	1
7-71-077	FRONT PANEL	1
5-01-256 5-01-258	120V BOTTOM COVER 230V BOTTOM COVER	1
7-01-078	LENS ACRYLIC	1
1-42-013	KEYPAD FOR PANEL	1
3-61-009A	LOGO BADGE	1
1-40-063	RUBBER FOOT K137	4
1-01-117 1-01-084	T1 120V TOROIDAL TRANS. T1 230V TOROIDAL TRANS.	1 1
3-71-088	HEAT SINK	1
3-71-062	HEAT SINK FOR 7805	1
3-71-061	HEAT SINK FOR 7809	1
1-09-092	LM1876TF	3
	MAIN PCB	1
1-43-003	2 RCA JACK HSP-212V-09 GP	3
1-08-0006	REGULATOR 7809	1
1-08-158	REGULATOR 7805	1
1-44-119	SPEAKER TERMINAL HSP-104HL-05	3
1-51-367 1-51-356	120V AC CORD 230V AC CORD	1 1
1-29-116 1-29-098	120V FUSE 3A GMA TYPE 230V FUSE 1.6A GMA TYPE	1
1-29-011 1-29-012	120V FUSE HOLDER 230V FUSE HOLDER	1
1-44-469	WIRE BUSHING	1
1-25-215	LD1 LED DISPLAY SET	1
1-05-032	2601-5P DISPLAY PCB	1
1-33-378	SCREW 3x8 TTS BZ FOR THE RUBBER FEET	4
1-33-341	SCREW 3x6 TTS-BH BZ FOR PCB & COVER	13
1-33-380	SCREW 3x8 BT BZ FOR RCA JACK & HEATSINK	14
1-34-280	SCREW 2.6x6 KM BZ FOR KEY PCB	6
1-33-300	SCREW 3x6 BT BZ -7809 HEATSINK	3
1-34-270	SCREW 2.6x6 BT BZ FOR DISPLAY	13
	5-01-257 5-01-262 7-71-077 5-01-258 7-01-078 1-42-013 3-61-009A 1-40-063 1-01-117 1-01-084 3-71-062 3-71-061 1-09-092 1-43-003 1-08-158 1-44-119 1-51-367 1-51-356 1-29-116 1-29-098 1-29-012 1-44-469 1-25-215 1-05-032 1-33-378 1-33-380 1-34-280 1-34-280	5-01-262 230V TOP COVER 7-71-077 FRONT PANEL 5-01-256 120V BOTTOM COVER 5-01-258 230V BOTTOM COVER 7-01-078 LENS ACRYLIC 1-42-013 KEYPAD FOR PANEL 3-61-009A LOGO BADGE 1-40-063 RUBBER FOOT K137 1-01-117 T1 120V TOROIDAL TRANS. 1-01-084 T1 230V TOROIDAL TRANS. 3-71-088 HEAT SINK 3-71-062 HEAT SINK FOR 7805 3-71-061 HEAT SINK FOR 7809 1-09-092 LM1876TF MAIN PCB 1-43-003 2 RCA JACK HSP-212V-09 GP 1-08-0006 REGULATOR 7809 1-08-158 REGULATOR 7809 1-08-158 REGULATOR 7805 1-44-119 SPEAKER TERMINAL HSP-104HL-05 1-51-367 120V AC CORD 1-29-116 120V FUSE 3A GMA TYPE 1-29-098 230V FUSE 1.6A GMA TYPE 1-29-011 120V FUSE HOLDER 1-29-012 230V FUSE HOLDER 1-44-469 WIRE BUSHING 1-25-215 LD1 LED DISPLAY PCB 1-33-378 SCREW 3x8 TTS BZ FOR THE RUBBER FEET 1-33-341 SCREW 3x8 TTS BT FOR PCB & COVER 1-33-380 SCREW 3x8 BT BZ FOR RCA JACK & HEATSINK 1-34-280 SCREW 3x6 BT BZ -7809 HEATSINK 1-34-270 SCREW 2.6x6 BT BZ


# **PACKING SECTION**


BATTERY	1-01-102	BATTERY GP24G 1.5V SIZE AAA ZINC CHLORIDE BATT. PACKAGE 2 IN 1	2
RCA Y-CABLE	1-51-136	WIRE, 2 RCA PHONE PLUG RED(R)/BLK(L) PLUG, +3.5mm STEREO PLUG/BLK, WITH 2MT 2C100121/2C28012SX2652P BLK SPIRAL SHIELD WIRE	1
RCA CABLE	1-51-316	WIRE, 1MT 100121/28012SSX2652P BLK PLUG, SPIRAL SHIELD WIRE RCA PHONE PLUG NICKLE-PLATED RED/BLK BOTH END	2
WIRES	HEC041-00	SPEAKER WIRES	6
OWNER'S MANUAL	0/M ESC200	ESC200 MANUAL	1
REMOTE	9-01-121	REMOTE CONTROL	1
FEET	1-33-378	RUBBER FEET	4
SATELLITES	J-SP-SAT	ESC200 SATELLITE SPEAKERS	5
SUBWOOFER	J-SP-SUB	ESC200 SUBWOOFER	1
CARTON	XRC145-00	DISPLAY CARTON	1

























# **INTEGRATED CIRCUIT DIAGRAMS**


#### IC U1 - NJM2177AL Dolby Pro-Logic Surround Decoder




#### IC U2 - NJU9701D/NJU9702D Digital Delay



IC U3 - CD 4066D **QUAD BILATERAL SWITCH** 




IC U4 - BA14741 ROM QUAD OP AMP





# **INTEGRATED CIRCUIT DIAGRAMS**

#### IC U5, U10, U11, U12 - BA4560/4560D DUAL OP-AMP




### IC U6, U7, U8 - LC7538NM ELECTRONIC VOLUME CONTROL







IC U18 - UPD75106CW-240 NEC-2552B MICROPROCESSOR




#### IC U13, U14, U15 - LM1876TF 20W POWER AMP







IC U16 - NJM7809FA/7809A +9V REGULATOR IC U17 - NJM7805FA/7805A +5V REGULATOR




# SCHEMATIC DIAGRAM 1 120V VERSION




# SCHEMATIC DIAGRAM 2 120V VERSION




# **SCHEMATIC DIAGRAM 3 120V VERSION**




# **SCHEMATIC DIAGRAM 4 120V VERSION**




# **SCHEMATIC DIAGRAM 1 230V VERSION**



# **SCHEMATIC DIAGRAM 3 230V VERSION**



# **SCHEMATIC DIAGRAM 4 230V VERSION**



# **ESC200 IC VOLTAGE READINGS**

# IC VOLTAGE CHART OF ESC200

#### CPU(2552B) U18

PIN	VOLT	PIN	VOLT
1	5	33	5
2	5	34	5
3	5	35	5
4	0.1	36	5
5	0	37	0
6	0	38	0
7	0	39	0
8	0	40	5
9	0	41	5
10	0	42	5
11	4.9	43	5
12	4.9	44	5
13	4.9	45	5
14	5	46	2.6
15	5	47	2.5
16	0	48	0
17	0	49	0
18	0	50	0
19	4.1	51	2
20	4.1	52	2
21	4.1	53	2
22	4.1	54	3
23	5	55	3
24	5	56	5
25	5	57	5
26	5	58	5
27	4.1	59	5
28	8.7	60	0
29	0.1	61	5
30	0.1	62	0
31	0	63	5
32	5	64	0

#### N.IM2177A U1

PIN	VOLT	PIN	VOLT
1	3.9	29	4
2	3.9	30	4.1
3	4	31	5.1
4	4.1	32	4
5	4	33	4
6	4.1	34	4
7	4	35	4.1
8	4	36	4.1
9	4	37	9
10	4	38	4.1
11	4	39	4.1
12	0	40	1.4
13	8.2	41	4
14	3.7	42	4.1
15	4	43	4.1
16	4	44	4.1
17	4	45	4.1
18	4	46	4.1
19	4	47	4.1
20	4	48	4.1
21	4	49	0
22	4	50	4
23	5	51	4
24	5	52	4
25	5	53	4
26	4.1	54	4
27	4.1	55	4
28	2.7	56	4

#### 14741 U4

PIN	VOLT	PIN	VOLT
1	4.1	8	4.1
2	4.1	9	4.1
3	4.1	10	4.1
4	9	11	0
5	4.1	12	4.1
6	4.1	13	4.1
7	4.1	14	4.1

# NJU9701\NJU9702 U2

PIN	VOLT	PIN	VOLT
1	5.1	13	2.6
2	2.2	14	2.6
3	2.4	15	2.6
4	5	16	2.6
5	5	17	0.7
6	0.1	18	0.7
7	0	19	2.6
8	5.1	20	2.6
9	0	21	2.6
10	0	22	2.6
11	0	23	2.6
12	0	24	5.1

#### LC7821 U9

LO7021 03			
PIN	VOLT	PIN	VOLT
1	4.1	16	0
2	4.1	17	0
3	4	18	9
4	4.1	19	9
5	4	20	0
6	4	21	0.3
7	4.1	22	0
8	4.1	23	4.1
9	0	24	4.1
10	0.3	25	4
11	0	26	4
12	-8.2	27	4.1
13	0	28	4
14	8.7	29	4.1
15	0.1	30	4.1

#### 4560 U5,U11-12

PIN	VOLT	PIN	VOLT
1	4.1	5	4.1
2	4.1	6	4.1
3	4.1	7	4.1
4	0	8	9

#### 4066D U3

PIN	VOLT	PIN	VOLT
1	1.3	8	2.6
2	1.4	9	2.6
3	4.1	10	2.6
4	2.6	11	2.6
5	0	12	0
6	5	13	5.1
7	0	14	5.1

#### LC7538 U6-8

PIN	VOLT	PIN	VOLT
1	4.5	19	0.1
2	4.5	20	0
3	4.5	21	0
4	4.6	22	0
5	4.6	23	1.4
6	4.6	24	0
7	4.6	25	0
8	4.6	26	0
9	0.2	27	4.6
10	4.6	28	1.4
11	4.6	29	4.6
12	4.6	30	8
13	4.6	31	4.6
14	4.6	32	8
15	4.6	33	4.6
16	9	34	4.6
17	0	35	4.6
18	8.6	36	4.6

#### LM1876 LI13-15

LIVI 1876 U 13-15			
PIN	VOLT	PIN	VOLT
1	0	9	0.1
2	22	10	0
3	0	11	0.1
4	-22	12	0
5	0	13	0
6	0.1	14	0.1
7	0	15	22
8	0		